

KYNAR FLEX®

TECHNICAL DATA SHEET

KYNAR FLEX® LBG 8200 POWDER

FLUORINATED COPOLYMER POWDER

KYNAR FLEX® LBG 8200 is a copolymer of vinylidene fluoride and hexafluoropropylene specifically designed to bring a high level of adhesion between the separator and the battery electrodes.

Main Characteristics:

- High adhesion
- Fast dissolution in typical solvents
- High molecular weight

DESIGNATION

PVDF

DELIVERY FORM

- Powder

RHEOLOGICAL PROPERTIES

속성	값	테스트 표준
Melt viscosity, 230°C (445°F) at 100 s-1	68 - 78 kPo	ASTM D3835
속성	값	테스트 표준
Melting temperature, 10°C/min	142-148 °C (293 °F)	ASTM D3418

OTHER PROPERTIES

속성	값	테스트 표준
Specific gravity, 23°C (73°F)	1.78 g/cm³	

SPECIAL CHARACTERISTICS

- Flame & smoke

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

ARKEMA