

## TECHNICAL DATA SHEET

# KYNAR® FLEX LBG 2200LX

## FLUORINATED COPOLYMER PELLET

Kynar Flex® LBG2200LX is a lithium ion battery grade latex of vinylidene fluoride and hexafluoropropylene designed for high performance.

### Main Characteristics:

- Same backbone as the well-known Kynar Flex® LBG grade
- High solid content
- Very stable latex

### DESIGNATION

PVDF

### DELIVERY FORM

- Latex

## RHEOLOGICAL PROPERTIES

속성	값	테스트 표준
Melt viscosity, 230°C (445°F) at 100 s-1	32-37 kPo	ASTM D3835
Solution viscosity	< 10 cPo	
	>30	
속성	값	테스트 표준
Melting temperature, 10°C/min	148-154	ASTM D3418
	100 °C	
Thermal Degradation temperature	> 270 °C	

## OTHER PROPERTIES

속성	값	테스트 표준
pH	3-4	
Solution viscosity	<10 cPo	
Active content	27-31 %	
Specific gravity	1.1 g/cm <sup>3</sup>	
	2-10	
	<1.10 µm	
	0.1-0.2 µm	
	10e14-10e15	
	5-9	

# KYNAR® FLEX LBG 2200LX

## SPECIAL CHARACTERISTICS

- Flame & smoke

**Headquarter: Arkema France**  
420, rue d'Estienne d'Orves  
92705 Colombes Cedex – France  
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.  
Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790

[arkema.com](https://www.arkema.com)

**ARKEMA**