

TECHNICAL DATA SHEET

PLATAMID[®] H 1937 PELLETT

COPOLYAMIDE PELLETT

PLATAMID H 1937 PELLETT is a thermoplastic copolyamide hot melt adhesive. This grade is designed to manufacture of hot melt film and webs by extrusion. It has good adhesion to all kinds of textile substrates based on native and synthetic fibers. This product is available dried with optical brightener (H 1937 TA).

DESIGNATION

PA*

DELIVERY FORM

- Pellets

TRANSFORMATION PROCESSES

- Filament extrusion

RHEOLOGICAL PROPERTIES

속성	값	테스트 표준
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	18 cm ³ /10min	ISO 1133
속성	값	테스트 표준
Melting temperature, 10°C/min	102 °C	ISO 11357-1/-3

PACKAGING

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 26 kg / 55 lb bags
- 501 kg big bag

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80