

## TECHNICAL DATA SHEET

# PLATAMID® H 2513 POWDER

## COPOLYAMIDE POWDER

PLATAMID H 2513 POWDER is a thermoplastic copolyamide hot melt adhesive. This medium melt viscosity grade is used for the production of fusible interlinings. It offers an excellent laundry resistance up to 60°C and an excellent resistance to all kind of steam treatment.

This product is available in different grain sizes:

- PA 80 (0-80 µm paste dot)
- PTA 170/20 (0-170 µm powder dot)
- PTA 170 (80-170 µm double dot)

### DESIGNATION

PA\*

### MAIN APPLICATIONS

- Adhesives - Apparel/Interlining

### DELIVERY FORM

- Powder

### TRANSFORMATION PROCESSES

- Scattering, paste, double dot

## RHEOLOGICAL PROPERTIES

プロパティ	価値	テスト基準
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	30 cm <sup>3</sup> /10min	ISO 1133

## THERMAL PROPERTIES

プロパティ	価値	テスト基準
Melting temperature, 10°C/min	128 °C	ISO 11357-1/-3

## 包装

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 20 kg / 44 lb bags
- 500 kg big bag

## 賞味期限

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

**Headquarter: Arkema France**  
420, rue d'Estienne d'Orves  
92705 Colombes Cedex – France  
T +33 (0)1 49 00 80 80