

TECHNICAL DATA SHEET

PLATAMID® H 2513 POWDER

COPOLYAMIDE POWDER

PLATAMID H 2513 POWDER is a thermoplastic copolyamide hot melt adhesive. This medium melt viscosity grade is used for the production of fusible interlinings. It offers an excellent laundry resistance up to 60°C and an excellent resistance to all kind of steam treatment.

This product is available in different grain sizes:

- PA 80 (0-80 µm paste dot)
- PTA 170/20 (0-170 µm powder dot)
- PTA 170 (80-170 µm double dot)

DESIGNATION

PA*

DELIVERY FORM

- Powder

TRANSFORMATION PROCESSES

- Scattering, paste, double dot

RHEOLOGICAL PROPERTIES

속성	값	테스트 표준
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	30 cm ³ /10min	ISO 1133
속성	값	테스트 표준
Melting temperature, 10°C/min	128 °C	ISO 11357-1/-3

PACKAGING

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 21 kg / 44 lb bags
- 501 kg big bag

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80