

## TECHNICAL DATA SHEET

# PLATAMID® H 2516 PELLETT

## COPOLYAMIDE PELLETT

PLATAMID® H 2516 PELLETT is a thermoplastic copolyamide hot melt adhesive. This fast re-crystallizing grade has been developed to manufacture hot-melt webs, nets and mono- and multi-filaments. It provides elastomeric properties and high water vapor transmission rate and it offers a very good adhesion to all kinds of textile substrates based on native and synthetic fibers. This product is available undried with optical brightener (H 2516 FA).

### DESIGNATION

PA\*

### DELIVERY FORM

- Pellets

### TRANSFORMATION PROCESSES

- Melt Spinning

## RHEOLOGICAL PROPERTIES

속성	값	테스트 표준
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	85 cm <sup>3</sup> /10min	ISO 1133
속성	값	테스트 표준
Melting temperature, 10°C/min	108 °C	ISO 11357-1/-3

## PACKAGING

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 501 kg big bag
- 501 kg / 1100 lb rigid containers

## SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

**Headquarter: Arkema France**  
420, rue d'Estienne d'Orves  
92705 Colombes Cedex – France  
T +33 (0)1 49 00 80 80