

TECHNICAL DATA SHEET

PLATAMID® H 2519 PELLETT

COPOLYAMIDE PELLETT

PLATAMID® H 2519 PELLETT is a thermoplastic copolyamide hot melt adhesive. It is partially manufactured from a renewable and sustainable source (castor oil). This medium melt viscosity, fast re-crystallizing grade is particularly suitable for manufacturing of webs, nets, mono- and multi-filaments, and films by extrusion. It exhibits strong adhesion onto:

- rigid and plasticized PVC as well as ABS, epoxy resin, PU, etc.
- various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.)

Dense layers of PLATAMID® H 2519 PELLETT are known to have barrier properties against PVC plasticizer migration.

This product is available:

- dried (H 2519 T)
- undried (H 2519 F)

DESIGNATION

PA*

MAIN APPLICATIONS

- Performance Wire
- Internal Components
- Adhesives - Automotive Interior

DELIVERY FORM

- Pellets

TRANSFORMATION PROCESSES

- Filament extrusion
- Melt Spinning

RHEOLOGICAL PROPERTIES

プロパティ	価値	テスト基準
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	8 cm ³ /10min	ISO 1133

OTHER PROPERTIES

プロパティ	価値	テスト基準
Bio-based carbon content, Measured	50 %	ASTM D6866
Specific gravity, 23°C (73°F)	1.09 g/cm ³	ISO 1183-1

包装

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 25 kg / 55 lb bags
- 500 kg big bag
- 500 kg / 1100 lb rigid containers

賞味期限

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

SPECIAL CHARACTERISTICS

- Bio-based
- Versatile adhesion

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80