

TECHNICAL DATA SHEET

PLATAMID® HX 2544 PELLETT

COPOLYAMIDE PELLETT

PLATAMID® HX 2544 PELLETT is a thermoplastic copolyamide hot melt adhesive. It is partially manufactured from a renewable and sustainable source (castor oil). This very low melt viscosity grade is particularly suitable for manufacturing of webs, nets, mono- and multi-filaments, and films by extrusion. It offers a good adhesion at low fusing conditions to various polar substrates (thermoplastics, thermosets, metal natural fibers, and more) and has good dry cleaning resistance and washing resistance up to 60°C.

This product is available:

- dried with optical brightener (HX 2544 TA)
- undried with optical brightener (HX 2544 FA)

DESIGNATION

PA*

DELIVERY FORM

- Pellets

RHEOLOGICAL PROPERTIES

속성	값	테스트 표준
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	104 cm ³ /10min	ISO 1133
속성	값	테스트 표준
Melting temperature, 10°C/min	95 °C	ISO 11357-1/-3

PACKAGING

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 26 kg / 55 lb bags

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

SPECIAL CHARACTERISTICS

- Bio-based

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80