

TECHNICAL DATA SHEET

PLATAMID[®] HX 2592 PELLET

COPOLYAMIDE PELLET

PLATAMID[®] HX 2592 PELLET is a thermoplastic copolyamide hot melt adhesive. It is manufactured from a renewable and sustainable source (castor oil). This low to medium melt viscosity grade is particularly suitable for manufacturing of webs, nets, mono- and multi-filaments, and films by extrusion. It exhibits strong adhesion onto:

- rigid and plasticized PVC as well as ABS, epoxy resin, PU, etc.
- various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.)

Dense layers of PLATAMID[®] HX 2592 PELLET are known to have barrier properties against PVC plasticizer migration.

This product is available:

- dried (HX 2592 T)
- undried (HX 2592 F)

DESIGNATION

PA*

DELIVERY FORM

- Pellets

RHEOLOGICAL PROPERTIES

속성	값	테스트 표준
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	24 cm ³ /10min	ISO 1133
속성	값	테스트 표준
Melting temperature, 10°C/min	106 °C	ISO 11357-1/-3

OTHER PROPERTIES

속성	값	테스트 표준
Bio-based carbon content, Measured	82 %	ASTM D6866
Specific gravity, 23°C (73°F)	1.09 g/cm ³	ISO 1183-1

PACKAGING

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 26 kg / 55 lb bags
- 501 kg big bag

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

SPECIAL CHARACTERISTICS

- Bio-based
- Versatile adhesion

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80