

TECHNICAL DATA SHEET

PLATAMID[®] HX 2598 PELLETT

COPOLYAMIDE PELLETT

PLATAMID[®] HX 2598 PELLETT is a thermoplastic copolyamide hot melt adhesive. This medium melt viscosity grade is particularly suitable for manufacturing of webs, nets, mono- and multi-filaments, and films by extrusion. It offers a very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.). This grade is available undried with optical brightener (HX 2598 FA).

DESIGNATION

PA*

MAIN APPLICATIONS

- Adhesives - Automotive Interior

DELIVERY FORM

- Pellets

TRANSFORMATION PROCESSES

- Filament extrusion

RHEOLOGICAL PROPERTIES

プロパティ	価値	テスト基準
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	33 cm ³ /10min	ISO 1133

THERMAL PROPERTIES

プロパティ	価値	テスト基準
Melting temperature, 10°C/min	143 °C	ISO 11357-1/-3

OTHER PROPERTIES

プロパティ	価値	テスト基準
Specific gravity, 23°C (73°F)	1.11 g/cm ³	ISO 1183-1

包装

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 500 kg big bag

賞味期限

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80