

TECHNICAL DATA SHEET

PLATAMID® HX 2620 POWDER

COPOLYAMIDE POWDER

PLATAMID® HX 2620 POWDER is a thermoplastic copolyamide hot melt adhesive. This low melt viscosity grade is used to manufacture fusible interlinings. It offers good laundry resistance and good steam resistance at low/medium fusing conditions

This product is available in different grain sizes:

- PA80 (0-80 µm paste dot)
- PRA 170 (0-170 µm double dot)

DESIGNATION

PA*

MAIN APPLICATIONS

- Adhesives - Apparel/Interlining
- Coating Additives - Adhesive And Sealant
- Coatings
- Graphic Arts Additives -Transfer Paper
- Inks

DELIVERY FORM

- Powder

TRANSFORMATION PROCESSES

- Scattering, paste, double dot

RHEOLOGICAL PROPERTIES

PROPERTIES	VALUE	TEST STANDARD
Melt volume flow rate (MVR), 150°C / 2.16kg (302°F / 4.4 lb)	41.5 cm ³ /10min	ISO 1133

THERMAL PROPERTIES

PROPERTIES	VALUE	TEST STANDARD
Melting temperature, 10°C/min	124 °C	ISO 11357-1/-3

PACKAGING

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 20 kg / 44 lb bags

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790