

TECHNICAL DATA SHEET

PLATAMID® HX 2651 PELLETT

COPOLYAMIDE PELLETT

PLATAMID® HX 2651 PELLETT is a thermoplastic copolyamide hot melt adhesive. This low melt viscosity grade is particularly suitable for manufacturing of webs and nets by extrusion. It offers good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.) thanks to its amine functionality groups.

This product is available undried with optical brightener (HX 2651 FA).

DESIGNATION

PA*

DELIVERY FORM

- Pellets

TRANSFORMATION PROCESSES

- Filament extrusion
- Melt Spinning

RHEOLOGICAL PROPERTIES

속성	값	테스트 표준
Melt volume flow rate (MVR), 130°C / 2.16kg (266°F / 4.4 lb)	36 cm ³ /10min	ISO 1133
속성	값	테스트 표준
Melting temperature, 10°C/min	105 °C	ISO 11357-1/-3

PACKAGING

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 26 kg / 55 lb bags

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80