

TECHNICAL DATA SHEET

PLATAMID® HX 2667 POWDER

COPOLYAMIDE POWDER

PLATAMID® HX 2667 POWDER is a thermoplastic copolyamide hot melt adhesive. This medium melt viscosity grade is suitable for manufacturing of of fusible interlinings. It offers an excellent laundry resistance up to 60°C and an excellent resistance to all kind of steam treatment.

This product is available in different grain sizes:

- PA80 (0-80 µm paste dot)
- PTA 170/20 (0-170 µm power dot)
- PTA 170 (80-170 µm double dot)

DESIGNATION

PA*

MAIN APPLICATIONS

- Adhesives - Apparel/Interlining

DELIVERY FORM

- Powder

TRANSFORMATION PROCESSES

- Scattering, paste, double dot

RHEOLOGICAL PROPERTIES

| PROPERTIES | VALUE | TEST STANDARD |
|--|---------------------------|---------------|
| Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb) | 30 cm ³ /10min | ISO 1133 |

THERMAL PROPERTIES

| PROPERTIES | VALUE | TEST STANDARD |
|----------------------------------|--------|----------------|
| Melting temperature, 23°C (73°F) | 128 °C | ISO 11357-1/-3 |

PACKAGING

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 20 kg / 44 lb bags

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80

Disclaimer - Please consult Arkema's disclaimer regarding the use of Arkema's products on <https://www.arkema.com/global/en/products/product-safety/disclaimer/> which is incorporated herein by reference and made a part hereof.

Arkema France, a French société anonyme registered at the Trade and Companies Register of Nanterre under the number 319 632 790