

## TECHNICAL DATA SHEET PLATAMID® M 1276 PELLET

#### **COPOLYAMIDE PELLET**

PLATAMID® M 1276 PELLET is a thermoplastic copolyamide hot melt adhesive. It is partially manufactured from a renewable and sustainable source (castor oil). This medium melt viscosity, fast re-crystallizing grade is particularly suitable for manufacturing of of webs, nets, mono- and multi-filaments, and films by extrusion. It exhibits strong adhesion onto:

- rigid and plasticized PVC as well as ABS, epoxy resin, PU, etc.
- various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.)

Dense layers of PLATAMID® M 1276 PELLET are known to have barrier properties against PVC plasticizer migration.

This product is available:

- dried (M 1276 TE)
- undried (M 1276 F)

#### DESIGNATION

PA\*

#### MAIN APPLICATIONS

- · Footwear Upper
- Internal Components
- · Adhesives Automotive Interior

#### **DELIVERY FORM**

Pellets

#### TRANSFORMATION PROCESSES

- Filament extrusion
- Melt Spinning

#### RHEOLOGICAL PROPERTIES

プロパティ	価値	テスト基準
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	6 cm³/10min	ISO 1133

#### THERMAL PROPERTIES

プロパティ	価値	テスト基準
Melting temperature, 10°C/min	110 °C	ISO 11357-1/-3

#### OTHER PROPERTIES

プロパティ	価値	テスト基準
Bio-based carbon content, Measured	26 %	<b>ASTM D6866</b>
Specific gravity, 23°C (73°F)	1.1 g/cm³	ISO 1183-1

#### 包装

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 25 kg / 55 lb bags
- 500 kg big bag

#### 賞味期限

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.



# HPP - 2025-02-14 - Page: 2 / 2

### PLATAMID® M 1276 PELLET

#### SPECIAL CHARACTERISTICS

- Bio-based
- · Versatile adhesion

**Headquarter: Arkema France** 420, rue d'Estienne d'Orves 92705 Colombes Cedex – France T +33 (0)1 49 00 80 80

