

TECHNICAL DATA SHEET

PLATAMID® M 1422 PELLET

COPOLYAMIDE PELLET

PLATAMID® M 1422 PELLET is a thermoplastic copolyamide hot melt adhesive. This semi-crystallized grade is used in solvent based processes. It has been developed for use in the wire coating industry.

This product is available:

- undried (M 1422 F)
- undried (M 1422/1 F)

DESIGNATION

PA*

MAIN APPLICATIONS

- Adhesives - Apparel/Interlining
- Performance Wire
- Internal Components

DELIVERY FORM

- Pellets

RHEOLOGICAL PROPERTIES

プロパティ	価値	テスト基準
Melt volume flow rate (MVR), 230°C / 2.16 kg (445°F / 4.7 lb)	30 cm ³ /10min	ISO 1133

THERMAL PROPERTIES

プロパティ	価値	テスト基準
Melting temperature, 10°C/min	120 °C	ISO 11357-1/-3

包装

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 25 kg / 55 lb bags

賞味期限

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80