

TECHNICAL DATA SHEET

PLATAMID® M 2395 PELLETT

COPOLYAMIDE PELLETT

PLATAMID® M 2395 PELLETT is a thermoplastic copolyamide hot melt adhesive. This medium melt viscosity, fast re-crystallizing grade is particularly suitable for manufacturing of webs, nets, mono- and multi-filaments, and films by extrusion. It exhibits strong adhesion onto:

- rigid and plasticized PVC as well as ABS, epoxy resin, PU, etc.
- various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc.)

Dense layers of PLATAMID® M 2395 PELLETT are known to have barrier properties against PVC plasticizer migration.

This product is available dried (M 2395 T).

DESIGNATION

PA*

MAIN APPLICATIONS

- Adhesives - Automotive Interior

DELIVERY FORM

- Pellets

TRANSFORMATION PROCESSES

- Filament extrusion
- Melt Spinning

RHEOLOGICAL PROPERTIES

プロパティ	値	テスト基準
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	8 cm ³ /10min	ISO 1133

THERMAL PROPERTIES

プロパティ	値	テスト基準
Melting temperature, 10°C/min	107 °C	ISO 11357-1/-3

包装

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 100 kg / 220 lb rigid containers

賞味期限

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

SPECIAL CHARACTERISTICS

- Versatile adhesion

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80