

## TECHNICAL DATA SHEET

# PLATAMID<sup>®</sup> M 995 PELLETT

## COPOLYAMIDE PELLETT

PLATAMID<sup>®</sup> M 995 PELLETT is a thermoplastic copolyamide hot melt adhesive. This high melt viscosity grade is particularly suitable for manufacturing of films and masterbatches. It offers very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

This product is available:

- dried (M 995 T)
- undried (M 995 F)

### DESIGNATION

PA\*

### MAIN APPLICATIONS

- Adhesives - Apparel/Interlining
- Internal Components
- Adhesives - Automotive Interior

### DELIVERY FORM

- Pellets

## RHEOLOGICAL PROPERTIES

プロパティ	価値	テスト基準
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	2 cm <sup>3</sup> /10min	ISO 1133

## THERMAL PROPERTIES

プロパティ	価値	テスト基準
Melting temperature, 10°C/min	144 °C	ISO 11357-1/-3

## 包装

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 25 kg / 55 lb bags

## 賞味期限

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

Headquarter: Arkema France  
420, rue d'Estienne d'Orves  
92705 Colombes Cedex - France  
T +33 (0)1 49 00 80 80