

TECHNICAL DATA SHEET

PLATAMID[®] M 995 PELLETT

COPOLYAMIDE PELLETT

PLATAMID[®] M 995 PELLETT is a thermoplastic copolyamide hot melt adhesive. This high melt viscosity grade is particularly suitable for manufacturing of films and masterbatches. It offers very good adhesion to various polar substrates (thermoplastics, thermosets, metal, natural fibers, etc).

This product is available:

- dried (M 995 T)
- undried (M 995 F)

DESIGNATION

PA*

DELIVERY FORM

- Pellets

RHEOLOGICAL PROPERTIES

속성	값	테스트 표준
Melt volume flow rate (MVR), 160°C / 2.16kg (320°F / 4.4 lb)	2 cm ³ /10min	ISO 1133
속성	값	테스트 표준
Melting temperature, 10°C/min	144 °C	ISO 11357-1/-3

PACKAGING

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

- 26 kg / 55 lb bags

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

Headquarter: Arkema France
420, rue d'Estienne d'Orves
92705 Colombes Cedex – France
T +33 (0)1 49 00 80 80