

TECHNICAL DATA SHEET RILSAN® BLACK RDP 15-10 ES

POLYAMIDE 11 POWDER

RILSAN® electrostatic spray powders are thermoplastic polyamides obtained from renewable resources.

Outstanding characteristics: abrasion resistance, corrosion resistance, impact resistance, sound reduction, flexibility, low coefficient of friction.

DESIGNATION

PA11

DELIVERY FORM

Powder

TRANSFORMATION PROCESSES

· Electrostatic spraying

ADDITIVES

· Heat Stabilized

MECHANICAL PROPERTIES

| 속성 | DRY / COND VALUE* | 테스트 표준 |
|--|-------------------|------------|
| Coating impact, 23°C (73°F) | - / 160 J | ASTM D2794 |
| Abrasion resistance, Wheel CS 17, load 1 kg, 1000 cycles | - / 15 mg | ISO 9352 |

^{*}DRY: Dry As Molded (DAM) if pellet / Dry if powder.

COND: Conditionned.

| 속성 | 값 | 테스트 표준 |
|-------------------------------|-----------------------|----------------|
| Melting temperature, 10°C/min | 183-188 °C (366.8 °F) | ISO 11357-1/-3 |

OTHER PROPERTIES

| 속성 | 값 | 테스트 표준 |
|--|--------------------------------|-------------------|
| Salt spray test | Good adhesion after 2000 hours | ISO 9227 |
| Particle Size Distribution (PSD) (Coarse particles > 75 μm) | 2.5 % | ASTM D3451 |
| Particle Size Distribution (PSD) (Coarse particles > 106 μm) | 0.5 % | ASTM D3451 |
| Particle Size Distribution (PSD) (Coarse particles > 150 μm) | 0.2 % | ASTM D3451 |
| Approximate RAL number | 9005 | |
| Covering Efficiency (120 µm) | 0.14 kg/m² | Internal Arkema |
| Specific gravity of coating, 20°C (68°F) | 1.12 g/cm³ | ISO 1183-1 |
| Median particles (D50) | 30 μm | ISO 13320 |

PACKAGING

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

• 46 kg / 100 lb drums



RILSAN® BLACK RDP 15-10 ES

SHELF LIFE

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

SPECIAL CHARACTERISTICS

Bio-based

Headquarter: Arkema France 420, rue d'Estienne d'Orves 92705 Colombes Cedex – France T +33 (0)1 49 00 80 80

