

# TECHNICAL DATA SHEET RILSAN® PA11 ESY BLUE 7414

### **POLYAMIDE 11 POWDER**

RILSAN® electrostatic spray powders are thermoplastic polyamides obtained from renewable resources.

Outstanding characteristics: abrasion resistance, corrosion resistance, impact resistance, sound reduction, flexibility, low coefficient of friction.

#### **DESIGNATION**

**PA11** 

#### MAIN APPLICATIONS

· Powder Coating - Others

#### **DELIVERY FORM**

Powder

#### TRANSFORMATION PROCESSES

· Electrostatic spraying

#### **ADDITIVES**

Heat Stabilized

# **MECHANICAL PROPERTIES**

プロパティ	DRY / COND VALUE*	テスト基準
Hardness, Persoz, 23°C (73°F)	- / 270	ISO 1522
Abrasion resistance, Wheel CS 17, load 1 kg, 1000 cycles	- / 17 mg	ISO 9352

<sup>\*</sup>DRY: Dry As Molded (DAM) if pellet / Dry if powder. COND: Conditionned.

# THERMAL PROPERTIES

プロパティ	価値	テスト基準
Melting temperature, 10°C/min	183-188 °C (366.8 °F)	ISO 11357-1/-3
Vicat softening temperature, 50N at 50°C/h	181 °C	ISO 306



# **RILSAN® PA11 ESY BLUE 7414**

### OTHER PROPERTIES

プロパティ	 価値	テスト基準
Median particles (D50)	30 μm	ISO 13320
Water absorption, 24h	≤ 1 %	ISO 62
Approximate RAL number	5010	
Covering efficiency (100 µm)	0.20 kg/m²	Internal Arkema
Apparent density, Non compacted	0.44	ISO 1068
Apparent density, Compacted	0.62	ISO 1068
Particle Size Distribution (PSD) (Fine particles < 20 μm)	20 %	ISO 13320
Particle Size Distribution (PSD) (Coarse particles > 100 μm)	1 %	ISO 13320
Specific gravity of coating, 20°C (68°F)	1.18 g/cm <sup>3</sup>	ISO 1183-1
Salt spray test	Good adhesion after 2000 hours	ISO 9227

# 包装

This grade is delivered dried in sealed packaging ready to be processed. Available packaging:

20 kg / 44 lb bags

# 賞味期限

Two years from the date of delivery, when stored properly (sealed bags, appropriate moisture, UV protection and temperature). For any use above this limit, please refer to our technical services.

#### SPECIAL CHARACTERISTICS

Bio-based

Headquarter: Arkema France 420, rue d'Estienne d'Orves 92705 Colombes Cedex – France T +33 (0)1 49 00 80 80

